

# PRODUCT INFORMATION

## EDGE TAPE: 90-DAY

90-Day Edge Tape is a single sided tape made with a laminated polyethylene cloth and proprietary acrylic adhesive. This tape offers superior physical properties and easy handling compared with conventional masking, protection and repair tapes. 90-Day Edge Tape allows up to a 90-day\* application with no residue left behind\*.



NO RESIDUE\*



90-DAY CLEAN REMOVAL\*



TRU-TEAR TECHNOLOGY



HIGH TENSILE STRENGTH



### COMPOSITION

- LDPE laminated layer
- HDPE cloth layer
- LDPE laminated layer
- Acrylic adhesive



### FEATURES

- Residue free removal even after 90 days\*
- Easy to tear by hands straight: No cutting tool required
- Scrap-less: face to face contact of adhesive separates without damaging the adhesive
- Easy repositioning and no wrinkles
- ASTM E 84(UL 723): Class 1, Flame Spread Index 5, Smoke Developed Index 0



### PROPERTIES

CONTENT	UNIT	VALUES	TEST METHOD
Thickness	mil (mm)	6.3 (0.16)	PSTC 133
Peel Adhesion	oz / in (N/cm)	36 (4.0)	PSTC 101
Shear Adhesion	mil (mm)	3.9 (0.1)	PSTC 107
Breaking Strength	lb/in (N/cm)	34 (60)	PSTC 131
Elongation	%	15	PSTC 131
Temperature Use Range	°F	-40 to 200	Internal test method

Note: Typical values, not for specification or guarantee purpose

### CHARACTERISTICS

- Waterproof
- High chemical and solvent resistance
- Wide application temp. range
- High abrasion resistance
- High dimension stability

### AVAILABLE SIZES

RB90DET2164 2" x 164'

### FURTHER TECHNICAL INFORMATION

- To determine suitability test 90-Day Edge Tape on a small portion of the surface that is in a non-exposed area.
- Some additives in PVC may soften adhesive layer over time. This may cause adhesive residue.
- 90-Day Edge Tape may leave residue on some natural stones or change in quality of surfaces.
- An effective residue remover is a 91% IPA (isopropyl alcohol) available in most local pharmacies.
- 90-Day Edge Tape may peel off surfaces of delicate materials or old coatings.
- Use only on clean, dry surfaces.
- For best performance, use within 1 year after purchase.
- Store in a dark, cool place.

### CAUTIONS

- DO NOT use as an electrical insulation tape.
- Avoid prolonged contact with skin. May cause irritation.
- Variety of factors may impart the performance of 90-Day Edge Tape. Before use, please test internal method or application.

### SAFETY

SDS sheets for Ram Board products available by request.

\*90-Day Edge Tape is designed to be used to tape Ram Board to the floor. Remove within 90 days of application. Do NOT use as an electrical insulation tape. Do NOT use on delicate surfaces, such as unpainted or painted drywall, wall paper, natural stone, faux finishes, lacquer or surfaces with a tendency to peel. Use on metal surfaces is an acceptable application, but not recommended for longer than 30 days of application. Use only on clean, dry surfaces. Test on a small area before use. Clean removal feature depends on the adherent material, test conditions and surface conditions. In no event will Ram Board's aggregate liability exceed the amount paid for this product. Liability limited to replacement of tape or refund of purchase price. Distributed by Ram Board® Tinley Park, IL 60487 | www.ramboard.com

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product. © 2021 Ram Board, Inc. Product names & attributes trademark of Ram Board, Inc. where applicable.

### CUSTOMER SERVICE

8450 185th STREET  
TINLEY PARK, IL 60487

P 844 4NO MESS  
E customerservice@surfaceshields.com



ramboard.com