

PRODUCT INFORMATION

PRO SHEETS™

Pro Sheets offer superior surface protection through dense, 48" x 96" sheets that are 8X thicker than Builder's Paper*. Pro Sheets lay out fast, flat, seam together quickly, and are easier to cut and customize to your jobsite than standard hardboard or plywood.



HEAVY-DUTY



SPILL GUARD®



VAPOR-CURE®



RECYCLABLE



8X
THICKER
— THAN —
BUILDER'S PAPER*

FEATURES

- Heavy-Duty temporary floor protection
- Exclusive Vapor-Cure™ technology
- Spill Guard™ technology
- Lays out fast
- Non-staining
- Proudly made in the U.S.A.

ECO-FRIENDLY

- Recyclable
- Reusable
- FSC Certified



PROPERTIES

Caliper:	60 mil (nominal)
Moisture:	< 6.5%
Cobb (2 min):	Top: 32 Bottom: 44
Tensile Strength:	MD: 433.42 lbf XD: 115.43 lbf
Tear Resistance:	MD: 475.68 lbf XD: 157.91 lbf
Puncture Resistance:	77.74 lbf
Dynamic Puncture Resistance:	5 N
Permeability:	Vapor Permeable Substrate
Ideal Application Conditions:	60 - 80°F with 30 - 50% relative humidity

APPLICATIONS

- Construction
- Moving
- Remodeling
- Model Homes
- Drywall
- Painting
- Parties
- Temporary Protection

AVAILABLE SIZES

RBPS48968X 48" x 96" Sheets

INSTRUCTIONS

1. Sweep or vacuum all dirt and debris off surface to be covered.
2. Place sheets on surface as-needed.
3. Cut to desired length with utility knife.
4. Tape the seams (Ram Board Seam Tape).
5. When taping directly to the floor, consult the flooring manufacturer for recommended tape.
6. To reuse, sweep the surface and remove Pro Sheets.

HANDLING AND STORAGE

Store in a dry, cool and well-ventilated place away from open flame and other sources of ignition. Handle in accordance with good industrial hygiene and safety practice. Avoid contact with eyes. Ensure adequate ventilation. Avoid generation of dust. Do not breathe dust. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use spark-proof tools and explosion-proof equipment. Take precautionary measures against static discharges.

USES

Wood, Colored Concrete, Stone, Marble, Terrazzo, Tile, Linoleum, Vct, Epoxy, & More

SAFETY

SDS sheets for Ram Board products available by request.

*Based on the average / nominal thickness of Builder's Paper. Please contact Ram Board at (855) 848-8678 for details.

Disclaimer: Materials should be stored in the environment in which it is expected to perform. Deliver the materials to an environmentally controlled site. Do not deliver product to any jobsite or install product until the building is fully enclosed and protected from exterior weather conditions. For best performance, keep materials wrapped in original packaging until anticipated use. Failure to follow these provided instructions may result in warping or curling of the product. If experiencing a concern, please contact our customer service team at 1-844-466-6377 immediately for further instruction.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product. © 2021 Ram Board, Inc.

CUSTOMER SERVICE

8450 185th STREET
TINLEY PARK, IL 60487

P 844 4NO MESS
E customerservice@surfaceshields.com



ramboard.com