

PRODUCT INFORMATION

RAM BOARD PRO TAPE

Ram Board takes duct tape to the next level. Pro Tape™ is engineered with a modified adhesive coating that utilizes our exclusive Scrim Fiber System™ designed to hold up better than anything on the jobsite. This multi-stage coating process creates a stronger bond between layers, which also provides cleaner removal during projects.



HEAVY-DUTY



SCRIM FIBER SYSTEM



FEATURES

- Aggressive adhesive provides superior holding power
- Quick stick to a wide variety of smooth and rough surfaces
- Flexible backing conforms well to irregular surfaces
- Smooth unwind makes it easier to apply in the field
- Scrim Fiber System leaves a clean edge when torn by hand
- Lays flat prevents twisting and curling



APPLICATIONS

- Construction
- Moving
- Remodeling
- Model Homes
- Drywall
- Painting
- Parties
- Temporary Protection

CHARACTERISTICS

Backing	Polyethylene coated cloth
Adhesive	Synthetic rubber resin
Total Thickness	7.0 mils
Tensile	17 lbs. / in.
Adhesion	65 oz. / in.
Elongation	12%
Application Temperature	50°F - 104°F (10°C - 40°C)
Service Temperature	32°F - 176°F (0°C - 80°C)

AVAILABLE SIZES

RBPT2.5-180 2.5" x 180'

INSTRUCTIONS

1. Sweep or vacuum all dirt and debris off surface to be covered.
2. Cut tape to desired length.
4. Apply Pro Tape the intended surface.
5. Consult the surface manufacturer for recommended tape.

HANDLING AND STORAGE

Store tape in its original packaging away from direct sunlight and in a cool and dry area. For optimum performance, tape should be used within 12 months of date of shipment. Tape works best when applied to a surface that is clean, dry and free of grease, oil or other contaminants.

SAFETY

SDS sheets for Ram Board products available by request.

The information in this document was obtained from sources which we believe reliable. The information is provided without any warranty expressed or implied regarding its correctness. We do not assume responsibility for loss, damage or expense in any way connected with the handling, storage, use or disposal of the product.

*Based on the average / nominal thickness of Builder's Paper. Please contact Ram Board at (855) 848-8678 for details.

© 2021 Ram Board, Inc. Product names & attributes trademark of Ram Board, Inc. where applicable.

CUSTOMER SERVICE

8450 185th STREET
TINLEY PARK, IL 60487

P 844 4NO MESS
E customerservice@surfaceshields.com



ramboard.com